



The Flow Warehouse, Unit C4 Pegasus Court, Ardglen Road, Whitchurch, Basingstoke,
Hampshire RG27 7BP

Tel: +44 (0)1256 636333 Fax: +44 (0)1256 896004

SPECIFICATIONS

THE FLOW WAREHOUSE SERIES 1750 VARIABLE AREA FLOW METER

- The series 1750 flow meter will give an instantaneous flow rate
- Inlet from the BOTTOM outlet from the top
- High resolution ideal for calibration purposes
- Direct reading of instantaneous flow rate
- Polycarbonate safety cover
- Good range of standard flow rate
- Easy to read scale
- Elegant and robust design
- Easy in-situ tube removal and reinstallation
- Minimum maintenance
- Anodised aluminium chassis
- ¼, inch up to 1 inch BSP process connections
- Polycarbonate cover
- Nitrile seals
- Hard anodised aluminium or stainless steel floats
- Atmospheric pressure only
- Atmospheric temperature 20° C
- Accuracy ± 5 % FSD

Key features

- Good resolution ideal for calibration purposes
- Direct reading of instantaneous flow rate
- Easy to read scale
- Minimum maintenance
- Atmospheric pressure only
- Atmospheric temperature 20° C
- Accuracy ± 5 % FSD
- Elegant and robust design